

> Carbide Burs

Shank Information

ISO 314 FG standard:19mm




ISO 315 FG L:22 mm

ISO 316 FG XL:25 mm

ISO 204 right angle:22mm

ISO 205 right angle:26 mm

Burs Details



Maximum Recommended Speed

FG head diameter up to 018 300.000 rpm

FG head diameter up to 023 200.000 rpm

FG head diameter up to 027 120.000 rpm

RA head diameter up to 023 30.000 rpm

RA head diameter up to 025 and greater 20.000 rpm

PACKING

FG/RA: 5 or 10 pcs/blister, 100 pcs/box

HP: 10 pcs/blister



HOW TO ORDER ?

◎ FG1

S	ISO No.									
FG	005	006	008	010	012	014	016	018	021	023
RA		006	008	010	012	014	016	018	021	023
HP			008	010	012	014	016	018	021	023
US No.	1/4	1/2	1	2	3	4	5	6	7	8
Order No.										
FG1-FG-	1/4									
FG1-RA-		1/2								
FG1-HP-			1	2	3	4	5	6	7	8

FG1:

head shape of instruments

S:

shank (FG,RA,HP)

Order no :

shape-shank-US No. (FG1-FG-1/4)

BURS FOR CLINIC

HOT ◎ FG33



S	ISO No.								
FG	009	009	010	010	012	012	016	016	021
RA			010		012	012	016	016	021
HP	009		010		012	012	016	016	021
US No.	699	699L	700	700L	701	701L	702	702L	703
Order No.									
FG33-FG-	699	699L		700L				702L	
FG33-RA-			700		701	701L	702		703
FG33-HP-	699								

◎ FG11R



S	ISO No.		
FG	010	012	009
US No.	245	246	256
Order No.			
FG11R-FG-	245	246	256

HOT ◎ FG21R



S	ISO No.		
FG	008	010	012
US No.	1156	1157	1158
Order No.			
FG21R-FG-	1156	1157	1158

◎ FG23R



S	ISO No.				
FG	009	010	010	012	012
RA				012	
US No.	1169	1170	1170L	1171	1171L
Order No.					
FG23R-FG-	1169	1170	1170L		1171L
FG23R-RA-				1171	

HOT ◎ FG31R



L	ISO No.		
S			
FG	008	010	012
RA		010	012
HP	008	010	012
US No.	1556	1557	1558
Order No.			
FG31R-FG-	1556		
FG31R-RA-		1557	1558
FG31R-HP-	1556		